


GRINDEX2400

240V- FLOOR PREPARATION MACHINE INDUSTRIAL VACUUM

WHY BUY?


THE GRINDEX2400 FLOOR PREPARATION DUST EXTRACTOR FROM THE V-TUF LINE IS DESIGNED FOR EFFICIENT FLOOR SANDING DUST EXTRACTION. IT CONNECTS DIRECTLY TO SANDING MACHINES, ENSURING AIR QUALITY AND OPERATOR SAFETY. ITS CONICAL CARTRIDGE FILTER (35,000 CM²) IS ENCASED IN A METAL CYLINDER FOR SUPERIOR CONCRETE DUST CAPTURE AND FILTER PROTECTION. OVERSIZED RUBBER WHEELS AND A TELESCOPIC SYSTEM ENHANCE MOBILITY AND COMPACTNESS FOR EASY TRANSPORT. THE UNIT IS COMPATIBLE WITH A 45L PAINTED STEEL CONTAINER OR THE PRACTICAL LONGOPAC® ENDLESS BAG SYSTEM.



POWER



FILTER



CAPACITY

HIGHLIGHTS



SUCTION UNIT

The vacuum is generated by 2 by-pass motors. Each motor is managed by an independent switch, permitting the operator to control the intake performance. The motors are located in a sturdy casing, with an insulating sponge to maintain a low noise level.



FILTERING ELEMENT

The filtration is guaranteed by a sturdy polyester filtering cartridge. The cartridge is made to ensure large filter surface (35,000 cm²) in a compact space. This way air can pass through when the filter is dirty too. The filter is M Class (BIA | EN 60335-2-69) certified. It stops the particles till 1 micron, preserving the motors and the operator.



VIBRO CLEANING SYSTEM

A filter cartridge cleaning system by vibration that maintains maximum suction efficiency even after prolonged use of compact machines, without the need for operator intervention.



LONGOPAC®

The vacuumed material is collected in a 20-meter-long durable plastic bag, Longopac®. Positioned under the filter chamber, the adjustable bag allows safe disposal. Once full, the operator seals it above the material, which automatically falls into the bag. The sealed section can be safely cut and disposed of without direct contact.



TECHNICAL DATA

MOTOR

TYPE	BY-PASS
VOLTAGE	240V
MAXIMUM VACUUM	250MBAR
MAXIMUM AIR FLOW	380M ³ /H
NOISE LEVEL	72DB(A)
ENGINES	2
FREQUENCY	50/60HZ
POWER	3.5HP

PRIMARY FILTER

TYPE	CARTRIDGE
CLASS EN 60335-2-69	M-CLASS
MEDIA	ANTISTATIC POLYESTER
FILTER CLEANING	VIBRATION
FILTERING EFFICIENCY (IFA)	IFA/BGIA M-PES AL

MACHINE

SUCTION INLET	500 mm
DIMENSIONS	585 x 545mm
HEIGHT	1,395mm
WEIGHT	45Kg

Item No.	GRINDEX2400
Description	240V FLOOR PREPARATION SINGLE-PHASE WET&DRY INDUSTRIAL VACUUM CLEANERS



V-TUF.CO.UK
T +44(0) 1522 51 57 67
E ENQUIRIES@V-TUF.COM

V-TUF