

TH STAN



TORRENT 5 1200L BOWSER 200 BAR 15L/MIN 10HP DIESEL PRESSURE WASHER with pump cooling system

SPECIFICATION DIESEL - GEARBOXED SS PUMP

MODKING DECOLIDE (DAD) 200 (max)

250 rated pump

MAX PRESSURE (BAR):

TORRENT5BOW-1200

TORRENT 5 1200L BOWSER 200 BAR 15L/MIN 10HP DIESEL PRESSURE WASHER with pump cooling system

WORKING PRESSURE (BAR)	200 (max)
MAX FLOW (L/MIN)	15
PUMP TYPE:	SELF-PRIMING
GEARBOX DRIVEN:	LOW REV PUMP
ENGINE TYPE:	DIESEL
FUEL TYPE	Diesel or HVO FUEL
LOW OIL ALERT	YES
ENGINE & PUMP Lubricated with PL500 (as standard)	
CHEMICAL APPLICATION:	Yes (venturi type)
POWER RATING;	10hp
PUMP SUCTION:	Yes
HIGH PRESSURE HOSE REEL	with 20m or 40m of
hose (specify your choice)	
GUN AND LANCE KIT:	Yes - MSQ/SSQ type
DIMENSIONS LxWxH (cm):	384 X 158 X 135cm
WEIGHT:	320kg
BOWSER TANK SIZE:	1200 litre
HIGHWAY SPECIFICATION	



The V-TUF TORRENT 5BOW – 1200 LITRE towable bowser pressure washer with low revving pump, makes light work of removing heavy dirt and grime, for quick, easy, and effective cleaning. The 10HP diesel engine can be used with HVO fuel which is <u>not</u> a fossil and reduces carbon emissions by 90%. V-TUF industrial bowser power washers have been developed off the back of popular market needs to handle the toughest cleaning jobs with ease, providing a simple to use, mobile, and reliable pressure washer. Using a V-TUF pressure washer with a gearbox greatly increases the life of the pump, and all the wearing parts, saving you time and money on the long-term maintenance.

The well proven hot dipped galvanized chassis and impact resistant tank can be easily transported across all types of rough terrain. With a powerful 10HP Diesel electric start engine, providing a high-pressure water supply of 3000psi, the performance of this V-TUF pressure washer always delivers effective cleaning results, wherever required!

Key features:

• 1200 liter towable, bowser high pressure cleaner with highway specification, commonly for maintaining farms, councils, sports facilities and site work.

- 10HP Electric start loncin Diesel Engine 200 Bar Max, 15 L/Min.
- Anti vibration mountings for smooth running
- Gearbox Driven Extends Life of Pump.
- · Return to tank bypass keep the pump cool and Extends Life of Pump.
- Robust high pressure hose reel with 20m or 40m hose (please specification)
- Hot dip galvanized Chassis & Compact Robust Frame for the toughes
- Ultimate Cleaning Results!
- Tough Build & Highly versatile & Very Reliable.
- Easy To Maneuver Over Rough Terrain Simple to Operate.
- Highway specification

• Ideal For Traversing Over Rough Terrain or motor way towing. Please note: The current stock comes with blue tanks

> V-TUF.COM T +44(0) 1522 78 79 78 E ENQUIRIES@V-TUF.COM



