



SAFETY DATA SHEET PRESSURE LUBE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PRESSURE LUBE
Product number PL500

1.2. Relevant identified uses of the substance or mixture and uses advised against Identified

uses Engine & Pump oil.

1.3. Details of the supplier of the safety data sheet

Supplier FENCO GROUP LTD
 TILL BRIDGE LANE
 LN1 2SX
 01522 787978
 01522 515767
 01522 787838
 enquires@V-TUF.COM

1.4. Emergency telephone number

Emergency telephone (01522) 787978 Monday to Friday 8.00am to 4.30pm.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Not Classified
Environmental hazards Not Classified

Classification (67/548/EEC or - 1999/45/EC)

2.2. Label elements

Hazard statements EUH208 Contains U3-thio-1,2:1,3:2,3-tris(u-disulfido-k2S) 1,2,3-tris(dialkydthiocarbamato)-triangulo-trimolybdenum(iv) dialkydthiocarbamate. May produce an allergic reaction.

2.3. Other hazards

PRESSURE LUBE - PL500

No significant hazards. Material does not meet the criteria for PBT or vPvB in accordance with REACH annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|--|----------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC; BASEOIL - U | 60-100% |
|--|----------------|

| | |
|------------------------|----------------------|
| CAS number: 64742-54-7 | EC number: 265-157-1 |
|------------------------|----------------------|

| | |
|---|---|
| Classification Asp. Tox. 1 - H304 | Classification (67/548/EEC or 1999/45/EC) Xn; R65 |
|---|---|

| | |
|--|-------------|
| DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC; BASEOIL - U | 1-5% |
|--|-------------|

| | |
|------------------------|----------------------|
| CAS number: 64742-55-8 | EC number: 265-158-7 |
|------------------------|----------------------|

| |
|---|
| Classification Not Classified |
|---|

| | |
|--|-------------|
| LUBRICATING OILS(PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED | 1-5% |
|--|-------------|

| | |
|------------------------|----------------------|
| CAS number: 72623-87-1 | EC number: 276-738-4 |
|------------------------|----------------------|

| |
|---|
| Classification Asp. Tox. 1 - H304 |
|---|

| | |
|---|-------------|
| DISTILLATES(PETROLEUM) HYDROTREATED HEAVY PARAFFINIC | 1-5% |
|---|-------------|

| | |
|------------------------|----------------------|
| CAS number: 64742-54-7 | EC number: 265-157-1 |
|------------------------|----------------------|

| |
|---|
| Classification Asp. Tox. 1 - H304 |
|---|

| | |
|--|-------------|
| LUBRICATING OILS (PETROLEUM) C15-30, HYDROTREATED NEUTRAL OIL-BASED | 1-5% |
|--|-------------|

| | |
|---------------|----------------------|
| CAS number: – | EC number: 276-737-9 |
|---------------|----------------------|

| |
|---|
| Classification Asp. Tox. 1 - H304 |
|---|

| | |
|--|-------------|
| A MIXTURE OF ISOMERS OF: C7-9-ALKYL 3-(3,5-DI- TRANS-BUTYL-4-HYDROXYPHENYL)PROPIONATE | 1-5% |
|--|-------------|

| | |
|-------------------------|----------------------|
| CAS number: 125643-61-0 | EC number: 406-040-9 |
|-------------------------|----------------------|

| | |
|---|---|
| Classification Aquatic Chronic 4 - H413 | Classification (67/548/EEC or 1999/45/EC) R53 |
|---|---|

PRESSURE LUBE - PL500

| | |
|--|---|
| Zinc bis[o-(6-methylheptyl)] bis[o-(sec-butyl)] bis(dithiophosphate) | 1-5% |
| CAS number: 93819-94-4 EC number: 298-577-9 | |
| Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411 | |
| Reaction products of Benzeneamine, N-phenyl- with nonene(branched) | <1% |
| CAS number: 36878-20-3 EC number: 253-249-4 | |
| Classification Aquatic Chronic 4 - H413 | Classification (67/548/EEC or 1999/45/EC) R53 |
| NON CLASSIFIED COMPONENT | <1% |
| CAS number: – | |
| Classification Not Classified | Classification (67/548/EEC or 1999/45/EC) - |
| U3-thio-1,2:1,3:2,3-tris(u-disulfido-k2S) 1,2,3-tris(dialkydthiocarbamate)-triangulo-trimolybdenum(iv) dialkydthiocarbamate | <1% |
| CAS number: – EC number: 457-320-2 | |
| Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|--|
| General information | Remove affected person from source of contamination. |
| Inhalation | Remove affected person from source of contamination. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing stops, provide artificial respiration. |
| Ingestion | Get medical attention. Do not induce vomiting. |
| Skin contact | Wash skin thoroughly with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury. |

PRESSURE LUBE - PL500

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion Harmful: May cause lung damage if swallowed.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

Hazardous combustion products Fire creates: Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Aldehydes, Sulphur oxides, Incomplete combustion products, Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Advice for firefighters

Protective actions during firefighting Evacuate area. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material.

6.4. Reference to other sections

PRESSURE LUBE - PL500

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Static electricity and formation of sparks must be prevented. Storage tanks and other containers must be earthed.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions The container choice, for example storage vessel, may effect static accumulation and dissipation. Store in closed original container at temperatures between 5°C and 25°C.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description AVOID CONTACT WITH SKIN AND EYES.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³ mist

Short-term exposure limit (15-minute): WEL 10 mg/m³ mist

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC; BASEOIL - U

Long-term exposure limit (8-hour TWA): WEL 5.0 mg/m³ 5.0 mg/m³ inhalable fraction, mist

WEL = Workplace Exposure Limit

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC; BASEOIL - U (CAS: 64742-54-7)

DNEL Workers - Inhalation; : 5.4 mg/m³
Consumer - Dermal; : 1.2 mg/m³

LUBRICATING OILS(PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

DNEL Workers - Inhalation; Long term local effects: 5.4 mg/m³
Consumer - Inhalation; Long term local effects: 1.2 mg/m³

Reaction products of Benzeneamine, N-phenyl- with nonene(branched) (CAS: 36878-20-3)

DNEL Workers - Dermal; Long term systemic effects: 0.62 mg/kg
Workers - Inhalation; Long term systemic effects: 4.37 mg/m³
Consumer - Dermal; Long term systemic effects: 0.31 mg/kg
Consumer - Inhalation; Long term systemic effects: 1.09 mg/m³
Consumer - Oral; Long term systemic effects: 0.31 mg/kg

PNEC - Fresh water; 0.10 mg/l
- marine water; 0.01 mg/l
- Sediment (Freshwater); 132000 mg/kg
- Sediment (Marinewater); 13200 mg/kg
- Soil; 263000 mg/kg

8.2. Exposure controls

PRESSURE LUBE - PL500

Protective equipment



Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

Hygiene measures

Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Discard contaminated shoes and clothing. Do not eat, drink or smoke when using this product.

Respiratory protection

No special requirements under ordinary conditions of use and with adequate ventilation. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Environmental exposure controls

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|------------------------------------|
| Appearance | Viscous liquid. |
| Colour | Light brown. |
| Odour | Slight. |
| Flash point | > 200°C Pensky-Martens closed cup. |
| Vapour pressure | <0.1 mm Hg @ 20°C |
| Viscosity | 12.4-16.3 cSt @ 100°C |

9.2. Other information

| | |
|-------------------|--|
| Other information | DMSO Extract(mineral oil only), IP-346: < 3% wt. |
|-------------------|--|

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|------------|-------------------------|
| Reactivity | See sub sections below. |
|------------|-------------------------|

10.2. Chemical stability

| | |
|-----------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. |
|-----------|---|

10.3. Possibility of hazardous reactions

| | |
|------------------------------------|----------------------|
| Possibility of hazardous reactions | Will not polymerise. |
|------------------------------------|----------------------|

10.4. Conditions to avoid

| | |
|---------------------|--|
| Conditions to avoid | Excessive heat. High energy sources of ignition. |
|---------------------|--|

PRESSURE LUBE - PL500

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition None at ambient temperatures.
products

SECTION 11: Toxicological information

11.1. Information on toxicological effects Skin

corrosion/irritation

Skin corrosion/irritation Prolonged contact may cause redness, irritation and dry skin.

Serious eye damage/irritation

Serious eye damage/irritation May cause mild, short lasting discomfort to the eyes.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Data lacking.

Carcinogenicity

Carcinogenicity Data lacking.

Reproductive toxicity

Reproductive toxicity - fertility Data lacking.

Specific target organ toxicity - single exposure STOT

- single exposure Data lacking.

Specific target organ toxicity - repeated exposure STOT

- repeated exposure Data lacking.

Aspiration hazard

Aspiration hazard Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Inhalation

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

Ingestion

Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Skin contact

May cause irritation.

Eye contact

Irritating to eyes.

Toxicological information on ingredients.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC; BASEOIL - U

Acute toxicity - oral

Acute toxicity oral (LD₅₀
mg/kg) 5,100.0

Species Rat

PRESSURE LUBE - PL500

ATE oral (mg/kg) 5,100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀
mg/kg) 2,100.0

Species Rabbit

ATE dermal (mg/kg) 2,100.0

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC; BASEOIL - U

Acute toxicity - oral

Acute toxicity oral (LD₅₀
mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀
mg/kg) 2,200.0

Species Rabbit

ATE dermal (mg/kg) 2,200.0

Zinc bis[o-(6-methylheptyl)] bis[o-(sec-butyl)] bis(dithiophosphate)

Acute toxicity - oral

Acute toxicity oral (LD₅₀
mg/kg) 2,600.0

Species Rat

ATE oral (mg/kg) 2,600.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀
mg/kg) 3,160.0

Species Rabbit

ATE dermal (mg/kg) 3,160.0

Reaction products of Benzeneamine, N-phenyl- with nonene(branched)

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀
mg/kg) 3,000.0

PRESSURE LUBE - PL500

| | |
|--------------------|---------|
| Species | Rat |
| ATE dermal (mg/kg) | 3,000.0 |

U3-thio-1,2:1,3:2,3-tris(u-disulfido-k2S) 1,2,3-tris(dialkydthiocarbamate)-triangulo-trimolybdenum(iv) dialkydthiocarbamate

Acute toxicity - oral

| | |
|--|---------|
| Acute toxicity oral (LD ₅₀ mg/kg) | 2,500.0 |
|--|---------|

| | |
|---------|-----|
| Species | Rat |
|---------|-----|

| | |
|------------------|---------|
| ATE oral (mg/kg) | 2,500.0 |
|------------------|---------|

Acute toxicity - dermal

| | |
|--|---------|
| Acute toxicity dermal (LD ₅₀ mg/kg) | 2,500.0 |
|--|---------|

| | |
|---------|-----|
| Species | Rat |
|---------|-----|

| | |
|--------------------|---------|
| ATE dermal (mg/kg) | 2,500.0 |
|--------------------|---------|

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Material not expected to be harmful to aquatic organisms.

Ecological information on ingredients.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC; BASEOIL - U

Acute aquatic toxicity

Acute toxicity - fish LL₀, 96 hours: 100 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EL₀, 48 hours: 1000-10000 mg/l, Daphnia magna

Acute toxicity - aquatic plants EL₀, 72 hours: 100 mg/l, Pseudokirchneriella subcapitata

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC; BASEOIL - U

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: >100 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EL₅₀, 48 hours: >100000 mg/l, Daphnia magna

Acute toxicity - aquatic plants NOELR, 72 hours: >100 mg/l, Pseudokirchneriella subcapitata

Zinc bis[o-(6-methylheptyl)] bis[o-(sec-butyl)] bis(dithiophosphate)

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: 4.5 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 5.4 mg/l, Daphnia magna

PRESSURE LUBE - PL500

Acute toxicity - aquatic plants EC₈₀, 96 hours: 2.1 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms EC₅₀, 3 hours: >10000 mg/l, Activated sludge

Reaction products of Benzeneamine, N-phenyl- with nonene(branched) Acute

aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >100 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >100 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 96 hours: 870 mg/l, Algae

Acute toxicity - microorganisms IC₅₀, 3 hours: >100 mg/l, Activated sludge

U3-thio-1,2:1,3:2,3-tris(u-disulfido-k2S) 1,2,3-tris(dialkydthiocarbamate)-triangulo-trimolybdenum(iv) dialkydthiocarbamate

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: 94.8 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EL₅₀, 48 hours: 50 mg/l, Daphnia magna

Acute toxicity - aquatic plants EL₅₀, 72 hours: 9.62 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms IC₅₀, 3 hours: >100 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability Material- expected to be inherently biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Ecological information on ingredients.

Reaction products of Benzeneamine, N-phenyl- with nonene(branched)

Partition coefficient log Pow: 77.6

12.4. Mobility in soil

Mobility Product floats on water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

PRESSURE LUBE - PL500

13.1. Waste treatment methods

| | |
|----------------------------|--|
| General information | Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. |
| Disposal methods | Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion. |
| Waste class | European waste code: 13 02 05 |

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous goods for transport.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not determined

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|-----------------------------|--|
| National regulations | EH40/2005 Workplace exposure limits. Health and Safety at Work etc. Act 1974 (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. |
| EU legislation | Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). |

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by Technical manager

PRESSURE LUBE - PL500

| | |
|----------------------------------|--|
| Revision date | 28/10/2019 |
| Revision | 1 |
| Supersedes date | 19/06/2016 |
| SDS number | 20353 |
| Hazard statements in full | H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life. EUH208 Contains U3-thio-1,2:1,3:2,3-tris(u-disulfido-k2S) 1,2,3-tris(dialkydthiocarbamato)-triangulo-trimolybdenum(iv) dialkydthiocarbamate. May produce an allergic reaction. |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.