



RAPID DES - STATIC

STAINLESS COVERED
HOT WATER STATIC WASHER

DIESEL Models available

DES 1520	DES 2115
15 L/MIN	21 L/MIN
200 BAR	150 BAR
10HP	10HP

Accessories included:

DURAKLIX®
10M QUICK RELEASE HOSE & TRIGGER SYSTEM



WHY BUY RAPID DES - STATIC?

Compact, diesel engine driven hot water high pressure washer. Heavy duty galvanized steel tubular frame with crane attachment points. Stainless steel covers, and easy to use control panel. Ideal for fleet wash, graffiti removal, chicken house cleaning contractors.

Industrial Specification

RAPID STATIC MODEL:	RAPID DES 1520	RAPID DES 2115
WATER FLOW(LITRES PER MINUTE):	15	21
PRESSURE (BAR/PSI)	200	150
MOTOR POWER HP	10	10
CHEMICAL FEATURE	L.PRESS.	L.PRESS.
RUN SYSTEM PROTECTION	SAFETY VALVE	SAFETY VALVE
WATER TEMPERATURE	0-150°C	0-150°C
WEIGHT	200kg	200kg
DIMENSIONS (L X W X H) cm	132 X 72 X 90cm	





RAPID STATIC 415C

STAINLESS COVERED
HOT WATER STATIC WASHER

V-TÜF Features

- Fuel, Water and detergent protection filters
- 304 Stainless steel protective covers
- Heavy duty galvanized steel tubular frame with crane attachment points
- Large 22ltr fuel tank.
- Detergent flow regulator. Micro-Controllable
- High efficiency double pass heat exchanger
- Chemical injection system
- No. 1 Italian Crank shaft pump with ceramic and brass and components. Excellent spares availability.
- Gearbox transmission at 1450 RPM.
- Bypass valve & safety valve
- Pressure gauge.
- Burner control with flow switch and thermostat
- 24v low tension control system.
- Comes with DuraKlix ® 10m Quick swivel hose and gun system.



Triplex pump with ceramic plungers connecting rod system, brass head pump. Pressure regulator with built-in detergent suction. Fuel, water & detergent filters. Pressure gauge & thermostat. Safety valve. Steam valve.



Three 230v DC high efficiency vertical stainless steel AISI 430 boilers, with refractory cement base.



Optional Brass Automatic Accelerator, to offer extra fuel savings.



12v control panel. 12v auxiliary socket. Electric start (battery excluded). Warning light indicating power & fuel.



Air cooled diesel engine 15LD440 /15LD4401, setting 10HP 7.4kW at 3600RPM, self-winding start and 12v electric start, cylindrical shaft, 30 Amp alternator, dry air filter



Gearbox transmission at 1450 RPM.