

DD065BP Base plate mounted petrol engine pressure washer

SPECIFICATION HONDA Petrol Commercial

WORKING PRESSURE (BAR):	4 – 200 BAR
WORKING PRESSURE (PSI):	58 – 3000 PSI
MAX FLOW (L/MIN)	12
ENGINE FUEL TYPE:	Petrol
WATER MAX INLET TEMP:	0°C - 160°C
ENGINE TYPE:	Honda GX200
POWER:	6.5 HP
PUMP TYPE:	XHDDH325SS
OPTIONAL EXTRAS:	Priming Valve
	Suction kit
	Return to tank bypass
DIMENSIONS LxWxH (cm):	60 X 55 X 45cm
WEIGHT:	30kg

200 BAR

MAXIMUM
PRESSURE

**SAFETY
FEATURES**
– Low oil
cut out

**Suitable for
suction**

Mount a pressure washer unit to your tank, van or trailer bowser.

- Well proven system.
- Ideal combination of pressure to low for the best results and efficiency on 6.5HP
- Idea for pressure washing or watering kits.
- Optional extras such as suction, priming valve, return to tank bypass (to prevent your pump overheating).
- Add any length hose, hose reel and lance type to suit your application.
- Hand Adjustable pressure and flow options to suit the task.
- MSQ Quick release couplings
- Serviceable unit with parts and accessories easily available
- Please speak to us if you require specific accessories for your application, as we have many accessory options to make this the ideal tool for the job,

Item No.

Description

RRP INC VAT

DD065BP

BASE PLATE MOUNTED PETROL ENGINE PRESSURE WASHER

V-TUF.COM

T +44(0) 1522 78 79 78

E ENQUIRIES@V-TUF.COM

COMBAT
GRIME