









240V/110V- PROFESSIONAL FLOOR PREPARATION MACHINE



WHY BUY?

DESIGNED FOR EFFICIENCY AND VERSATILITY, THESE ERGONOMIC FLOOR MACHINES FEATURE A DURABLE STAINLESS STEEL CHASSIS AND A PPL-COATED BASE FOR ENHANCED PERFORMANCE. CHOOSE FROM MODELS WITH A BELT TRANSMISSION DRIVE SYSTEM, TAILORED FOR VARIOUS FLOOR TREATMENT APPLICATIONS.

TP 43 G

A HIGH-PERFORMANCE ELECTRIC FLOOR MACHINE WITH A NYLON GEAR DIRECT DRIVE TRANSMISSION, DELIVERING A DISC ROTATION SPEED OF 160 RPM—IDEAL FOR ROUTINE FLOOR MAINTENANCE. AN OPTIONAL 7 KG EXTRA WEIGHT CAN BE ADDED FOR INCREASED EFFECTIVENESS. THE DETACHABLE POWER CORD SIMPLIFIES TRANSPORTATION AND MAINTENANCE.

TP 43, TP 43 400 & TP 43 DS

PROFESSIONAL BELT-DRIVEN FLOOR MACHINES AVAILABLE IN DIFFERENT SPEED CONFIGURATIONS:

- TP 43 (180 RPM) IDEAL FOR DEEP CLEANING.
- TP 43 400 (400 RPM) DESIGNED FOR POLISHING AND DRY MAINTENANCE.
- TP 43 DS (180/400 RPM) A DUAL-SPEED MODEL FEATURING A PUSH-BUTTON SPEED SELECTOR FOR VERSATILITY.

THE BELT TRANSMISSION SYSTEM ENSURES QUIET OPERATION, MAKING THESE MACHINES SUITABLE FOR NOISE-SENSITIVE ENVIRONMENTS SUCH AS HOSPITALS AND NURSING HOMES.

TECHNICAL DATA

| DESCRIPTION | TP 43 | TP 43 400 | TP 43 DS |
|-----------------------------|---------------|---------------|---------------|
| DRIVE | BELT | BELT | BELT |
| RATED POWER (W) | 1100 | 1400 | 1100/1400 |
| NUMBER OF REVOLUTIONS (rpm) | 180 | 400 | 180/400 |
| BRUSH (Ø mm) | 430 | 430 | 430 |
| PAD HOLDER (Ø mm) | 430 | 430 | 430 |
| TANK CAPACITY (I) | 15 OPTIONAL | 15 OPTIONAL | 15 OPTIONAL |
| WEIGHT (Kg) | 35 | 35 | 35 |
| SIZE L x W x H (cm) | 46 x 56 x 120 | 46 x 56 x 120 | 46 x 56 x 120 |

