

## DELUGE 2000/1125 HWTDES Trailer Diesel driven HOT/COLD/STEAM bower site pressure washer – Suited for highway towing

### SPECIFICATION

|  |                                     |
|--|-------------------------------------|
| WORKING PRESSURE (BAR)                 | Models 150 to 200                   |
| MAX FLOW (L/MIN)                       | 15 to 21 (Optional)                 |
| PUMP TYPE:                             | SELF-PRIMING SUPER SERIES           |
| BOILER:                                | Large Diesel fired for hotter water |
| CHEMICAL APPLICATION:                  | Yes                                 |
| STEAM PRESSURE MODE:                   | Yes                                 |
| COLD WATER MODE:                       | Yes                                 |
| HOT WATER MODE:                        | Yes (adjustable temp)               |
| ADJUSTABLE PRESSURE:                   | Yes 0 to Max pressure               |
| ENGINE TYPE:                           | KOHLER 11HP DIESEL                  |
| POWER RATING:                          | 11HP                                |
| HIGH PRESSURE HOSE REEL:               | OPTIONAL                            |
| WATER SUPPLY REEL:                     | OPTIONAL                            |
| ACCESSORY STORAGE                      | Yes                                 |
| DIMENSIONS L x W x H (cm):             | 453 x 196 x 162cm                   |
| TOWING HEIGHT:                         | 450mm                               |
| ANTIFREEZE TANK:                       | Yes                                 |
| WATER TANK SIZES:                      | 1125 or 2000 liters                 |
| SUITABLE FOR FOSSIL FREE FUELS such as | HVO100/XTL etc                      |

Ideal for Site  
Work

HOT/COLD  
/STEAM  
CLEANING

Suited for  
HIGHWAY  
Towing

### Features:

- A Rugged Site HDT pressure washer suited for Highway towing.
- Available with 2000 litre or 1125 litre water tanks
- **Steam pressure mode:** Adjustable pressure
- **Aqua mode:** Adjustable water Temperature, pressure and flow
- **Weed control mode:** OPTIONAL
- Easy to use controls
- Key Start as standard with pull start if required.
- AIS – Auto Idle System – Engine goes back to idle when spray gun is released
- Lance & hose holder brackets
- Hose reel options for high-pressure hoses.
- Energy efficient multi-pass single boiler system more hot water with fuel saving
- Independent vibration control – less mechanical and electrical down time.
- Proven reliability
- Service friendly maintenance
- Ideal for hire, cleaning contractors and councils
- DELUGE2000HWTDES - Unladen weight: 800 KG; Gross Laden weight: 2800kg
- DELUGE1125 HWTDES - Unladen weight: 796 KG; Gross Laden weight: 1925kg



### Item No. Description

- **DELUGE2000HWTDES** V-TUF DELUGE 11HP 200bar, 15L/min DIESEL KOHLER 2000 ltr Highway Trailer Bowser HOT Pressure Washer (Electric Key Start)
- **DELUGE1125HWTDES** V-TUF DELUGE 11HP 200bar, 15L/min KOHLER 1125 ltr Highway Trailer Bowser HOT Pressure Washer (Electric Key Start)
- 150 bar 21 liter per minute models available

V-TUF.COM

T +44(0) 1522 78 79 78

E ENQUIRIES@V-TUF.COM

COMBAT GRIME

## DELUGE 2000/1125 HWTDES Trailer Diesel driven HOT/COLD/STEAM bower site pressure washer – Suited for highway towing

### FURTHER BOWSER SPECIFICATIONS

- **CHASSIS:** Constructed from 5mm pressed steel section fully welded with a front mounting plate and 100 x 50 RSC 'A' frame drawbar.
- **AXLE/SUSPENSION:** Single Knott-Avonride 3000kg torsion beam axle fitted with 300 x 60 auto reverse brakes.
- **WHEELS AND TYRES:** 2 no. 235 /85 x 16 x 12 ply radial tyres on 5 stud 61/2" pcd rims.
- **COUPLING:** Knott-Avonride 3000kg capacity posibrake over run auto reverse coupling c/w breakaway cable, spring assisted handbrake lever, fitted with 40mm eye or 50mm ball.
- **TANK:** Polyethylene moulded tank, elliptical in section, with internal anti surge baffle & fitted with a 22" lockable outer hinged manlid cover, inner sealed vented manlid. 2" front draw off, 2 rear outlet connections. Tank secured to chassis with 2 stainless steel straps.
- **ANCILLARY EQUIPMENT:** moulded mudguards, mud flaps, front telescopic jockey wheel, Side reflectors, & front markers, full road lighting c/w 13 pin plug, optional extra 7 pin adapter, available on request.
- **FINISH:** Polyethylene tank in Black. Chassis painted with double corrosive resistant protection as standard.
- **DIMENSIONS:** (approximate)
  - Width: 1.955 m (77")
  - Length: 4.527 m (178½")
  - Height: 1620 m (64")
  - Towing Height: (level) 450 mm

