

V-TUF



TORRENT 2 150 LITRE LONG RANGE BARROW BOWSER WASHER



150 LITRE

25% MORE WATER CAPACITY

ROBUST BUILD

ROTA MOULDED TANK

PROTECTION

LOW OIL, THERMAL FROST, BYPASS

FEATURES

MEGA 150 LITRE TANK OFFERING 25% LONGER CLEANING TIME THAN THE NEXT BEST ON THE MARKET
 ROTA MOULDED TANK FOR EXTRA DURABILITY
 EUROPEAN SPECIFICATION LONCIN PETROL ENGINE. RELIABLE & POPULAR PARTS
 15 METRE HIGH-PRESSURE HOSE FOR EXTRA 10 METRE CLEANING RANGE
 LARGE WHEELBARROW WHEELS, TIPPING POINT MOUNTED FOR EASY ONSITE MANOEUVRABILITY
 BYPASS USES TANK WATER A RADIATOR TO ENSURE PUMP RUNS COOL
 CLEAR BOWL FILTER TO PROTECT PUMP SYSTEM FORM DEBRIS & OFFERS EASY CLEANING
 LOW OIL CUT OUT TO PROTECT ENGINE FROM OVERHEATING
 STATIC TRIGGER & LANCE STORAGE FOR EASY ROBUST STOWAGE
 HOIST LIFT POINT FOR SITE AND CRANE LIFTING
 STATIC HOSE STORAGE FEATURE ELIMINATES THE NEED FOR ADDITIONAL HOSE REEL. COMPACT
 POWDERCOATED FRAME WITH STAINLESS FIXINGS SMART & ANTI CORROSIVE.
 ENTIRE CAGE SURROUND FOR PUMP & ENGINE GREAT PROTECTION AGAINST BUMPS
 COMPACT DESIGN ENSURES THAT IT CAN FIT THROUGH STANDARD DOORWAYS
 26% GREATER PRESSURE (2800PSI) EXCELLENT CLEANING PERFORMANCE WITH LOW WATER USAGE.

WHY BUY?

THE LATEST TORRENT 2 BY V-TUF HAS BEEN DEVELOPED OFF THE BACK OF POPULAR MARKET NEEDS.

SIMPLE ▶ MOBILE ▶ COMPACT ▶ RELIABLE ▶ MAXIMUM REMOTE CLEANING TIME

THE SMART ERGONOMICS ENABLE THE MASSIVE 150 LITRE UNIT TO BE TRANSPORTED OVER ROUGH TERRAIN EASILY BY ONE PERSON. THE CENTRAL HOIST POINT OFFERS FANTASTIC PORTABILITY. THROUGH STANDARD DOORWAYS, DOWN SHAFTS, ON TOP OF BUILDINGS, ETC. THE 2800 PSI PRESSURE DELIVERS FANTASTIC CLEANING PERFORMANCE WITH LOW WATER USAGE. THE RELIABILITY IS ACHIEVED BY THE COMBINATION OF THERMAL OVERLOAD PROTECTION, FROST PROTECTION, LOW OIL CUT OFF, TANK/RADIATOR TECHNOLOGY AND ROBUST, ANTI-CORROSIVE CONSTRUCTION. IT TRULY DELIVERS TOP CLEANING PERFORMANCE WHEREVER YOU WANT IT!

ACCESSORIES INCLUDED

QUICK RELEASE 15 METRE HOSE, ONE-PIECE, ROBUST GUN & LANCE KIT.

SPECIFICATION

PRESSURE	190 BAR 2800 PSI
ENGINE	PETROL HONDA / EURO LONCIN
FLOW RATE	8-13 LITRES PER MINUTE
DIMENSIONS	H:760xW:680xL:1600mm
WEIGHT	59KG (EMPTY)
PROTECTION	THERMAL
LOW OIL CUT OFF	YES
PRE-PUMP FILTER	YES
POWDERCOATED FRAME	YES

V-TUF

GET EQUIPPED

V-TUF.COM

T +44(0) 1522 51 57 67

E ENQUIRIES@V-TUF.COM

Item No:

V-TUF TORRENT 2

Item No:

150 LITRE LONG RANGE BARROW BOWSER WASHER