



JETWASH HOSE SPEC SHEET



	MAX WORKING PRESSURE (BAR)	MINIMUM BURST PRESSURE (BAR)	TEMPERATURE RANGE	BORE - ID(MAX) Ø	DIAMETER OD Ø	MINIMUM BEND RADIUS (mm)	WEIGHT (GRAMS PER METER)	APPLICATION	INNER TUBE	REINFORCEMENT	OUTER COVER
1/4 1 Wire	250	1120	-40 oC to 150 oC	1/4" 6.4mm	13.5	100	228	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion, Ozone and Weather Resistant Synthetic rubber
1/4 2 Wire	400	1650	-40 oC to 150 oC	1/4" 6.4mm	14.9	100	386	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion, Ozone and Weather Resistant Synthetic rubber
5/16 1 Wire	250	960	-40 oC to 150 oC	5/16" 8mm	15.5	115	265	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion, Ozone and Weather Resistant Synthetic rubber
5/16 2 Wire	400	1650	-40 oC to 150 oC	5/16" 8mm	16.9	115	427	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion, Ozone and Weather Resistant Synthetic rubber
3/8 1 Wire	250	820	-40 oC to 150 oC	3/8" 9.5mm	17.4	125	343	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion, Ozone and Weather Resistant Synthetic rubber
3/8 2 Wire	400	1600	-40 oC to 150 oC	3/8" 9.5mm	18.3	130	559	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion, Ozone and Weather Resistant Synthetic rubber
1/2 1 Wire	200	750	-40 oC to 150 oC	1/2" 12.7mm	20.5	180	420	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion, Ozone and Weather Resistant Synthetic rubber
1/2 2 Wire	400	1250	-40 oC to 150 oC	1/2" 12.7mm	22	180	651	For high pressure air, oil and water	Hot water, detergent and oil resistant synthetic rubber	Super Tension Braid Technology. Single Braid	Oil, Abrasion, Ozone and Weather Resistant Synthetic rubber

SWAGE DIMENSIONS GUIDE	1/4	5/16	3/8	1/2
1SN	17mm	17.5mm	20mm	22.5mm
2SN	17.5mm	18mm	21.5mm	24mm